



Vision Correction

Product Availability Varies Worldwide

Style	Material	Diameter	Treatment	Power Range	Colors
Single Vision					
FSV	Hard Resin	60mm	Uncoated	+0.25D to +6.00D sph on -2.50 cyl	Clear
FSV	Hard Resin	65mm	Uncoated, Hard Coated, AR Coated, Super AR Coated	+0.25D to +6.00D sph on -2.50 cyl	Clear
FSV	Hard Resin	70mm	Uncoated, Hard Coated, AR Coated, Super AR Coated	0.00D to -6.00D sph on -2.50 cyl	Clear
FSV	Hard Resin	70mm	Uncoated	+0.25D to +6.00D sph on -2.50 cyl	Clear
FSV	Polycarbonate	70mm	Hard Coated, AR Coated, Super AR Coated	+4.00D to -6.00D sph on -2.00 cyl	Clear
FSV Asph	Polycarbonate	65mm	Hard Coated, AR Coated, Super AR Coated	+0.25D to +6.00D sph on -2.00 cyl	Clear
SFSV	Hard Resin	70mm	Uncoated, Hard Coated	Base curves 0.50,2.00,4.25,5.25,6.25,7.25,8.25,9.25,10.25	Clear
SFSV	Polycarbonate	76mm	Hard Coated	Base curves 0.75,1.75,2.75,3.75,4.75,5.75,6.75,7.75,8.75	Clear
SFSV	Index 1.71	65/70/75mm	Hard Coated	Base curves 0.25,1.50,2.25,3.00,4.50,5.25,6.00,7.00,7.75,8.75,11.00	Clear

Multi Focals

SFFT 28	Hard Resin	70mm	Uncoated, Hard Coated	Base curves 0.50,2.00,4.25,5.25,6.25,8.25,10.50; adds from 0.75 to 6.00 (Uncoated); adds from 0.75 to 3.50 (Hard Coated)	Clear
SFFT 35	Hard Resin	70mm	Uncoated	Base curves 0.50,2.00,4.25,6.25,8.25,10.50; adds from 0.75 to 4.00	Clear
SFFT 28	Polycarbonate	76mm	Hard Coated	Base curves 0.75,2.75,4.75,6.75, 7.75; adds from 1.00 to 3.50	Clear
SF TRI 7x28	Hard Resin	70mm	Uncoated	Base curves 2.00,4.25,6.25,8.25,10.50; adds from 1.50 to 6.00	Clear
All Purpose F PAL	Hard Resin	75mm	Uncoated, Hard Coated	Base curves 1.50,3.25,5.25,7.25; adds from 0.75 to 3.50	Clear
All Purpose F PAL	Polycarbonate	70/76mm	Hard Coated	Base curves 0.75,2.75,4.75,6.75,7.75; adds from 1.00 to 3.50	Clear
Short Corridor M PAL	Hard Resin	70/75mm	Hard Coated	Base curves 2.00,4.25,5.75,7.75; adds from 1.00 to 3.50	Clear
Short Corridor M PAL	Polycarbonate	76mm	Hard Coated	Base curves 2.75,4.75,6.75,7.75; adds from 1.00 to 3.50	Clear

Sun Protection

Style	Material	Diameter	Treatment	Power Range	Colors
Photochromic					
FSV	SunSensors Index 1.56	65/70mm	Hard Coated, AR Coated	+4.00D to -6.00D sph on -2.00 cyl	Grey, Brown
SFSV	SunSensors Index 1.56	65/70mm	Hard Coated	Base curves 0.50 (65mm); 2.00, 4.25, 5.75, 7.75 (70mm)	Grey, Brown
SFFT 28	SunSensors Index 1.56	70mm	Hard Coated	Base curves 2.00,4.25,5.25,6.25,8.50; adds from 1.00 to 3.50	Grey, Brown
All Purpose F PAL	SunSensors Index 1.56	70/75mm	Hard Coated	Base curves 2.00,4.25,5.75 (75mm); 7.75 (70mm); adds from 1.00 to 3.50	Grey, Brown
Short Corridor M PAL	SunSensors Index 1.56	70/75mm	Hard Coated	Base curves 2.00,4.25,5.75 (75mm); 7.75 (70mm); adds from 1.00 to 3.50	Grey, Brown

Polarized

Plano	Hard Resin	78mm	Hard Coated	6 base and 8 base	Grey, Brown, Green
SFSV Decentered	Hard Resin	75mm	Hard Coated	Base curves 0.50,2.00,4.25,5.25,6.25,8.25	Grey, Brown, Green
SFFT 28	Hard Resin	70mm	Hard Coated	Base curves 2.00,4.25,5.25,6.25,8.25; adds from 0.75 to 3.50	Grey, Brown
All Purpose F PAL	Hard Resin	75mm	Hard Coated	Base curves 1.50,3.25,5.25,7.25; adds from 1.00 to 3.50	Grey, Brown